

Metal Seat Ball Valve

Standard Design Features

<ul style="list-style-type: none"> · Two Piece or Three Piece · Single / Double Piston Seat · Double Block & Bleed · Anti Blow-Out Proof Stem · Anti Static Device · Emergency Sealant Injection 	<ul style="list-style-type: none"> · Secondary Fire-Safe Metal to Metal Seat
--	---

Production Range

- Available Size : NPS 1/2" ~ 48" (DN 15 ~ DN 1,200)
- Pressure : ASME Class 150 to Class 2,500 (PN 20 ~ PN 420)
- Temperature : -46°C ~ 200°C
- Body Materials : Carbon Steel, Stainless Steel, Alloy Steel, Duplex Steel, Ni-Al Bronze
- Trim : Carbon Steel, Stainless Steel, Duplex Steel, Ni-Al Bronze
- End Connection : RF, RTJ, BW, FF
- Materials

Carbon Steel	Duplex Stainless Steel	Special Alloy Steel
ASTM A216 - WCB or Equivalent	ASTM A995 - 1A 2A 4A 5A or Equivalent	Inconel 625 825 or Equivalent Hastelloy C Monel or Equivalent
Alloy Steel	Stainless Steel	
ASTM A217 - WC6 WC9 C5 C12 C12A or Equivalent	ASTM A351 - CF8 CF8M CF3 CF3M CN7M or Equivalent	

Design Standards

- Design : API 6D, ISO 17292, ASME B16.34
- Face to Face : ASME B16.10
- End Flange : ASME B16.5
- Butt-Welding Ends : ASME B16.25
- Test : API 598, BS 6755, API 6D
- Fire Safe Test : API 607, API 6FA
- Special : NACE MR - 01 - 75, MR - 01 - 03

